

Flexibore[®] installation accessory



5 Tonne Lifting Clamp

IDEAL FOR

- All Flexibore hose
- Both Crane and Truck & Crane installation methods
- Installation and retrieval

Lifting Clamps are an essential accessory for the safe installation of your submersible pump with Flexibore.

Crane method installations are the most common for larger projects and require two **Lifting Clamps**.

Truck & Crane method installations will need two **Lifting Clamps** and the Flexibore Installation Roller.

Crusader Hose offers a range of **Lifting Clamps** to best suit your bore installation project with ratings from 1.2 Tonne to 7 Tonne.

FEATURES

- ✓ Swing bolts
- ✓ Engineered design
- ✓ Rated for different weights
- \checkmark Compliance tag



1.2 Tonne Lifting Clamp

TECHNICAL DATA



7 Tonne Lifting Clamp



Scan here to watch a Flexibore installation using lifting clamps

Lifting Clamp	1.2 Tonne	5 Tonne	7 Tonne
Hose range (ID)	32 mm - 152 mm	76 mm - 152 mm	152 mm - 254 mm
	1.25" - 6"	3" - 6"	6" - 10"
Material	Mild Steel, painted finish	Mild Steel, painted finish	Mild Steel, painted finish
Weight	11 kg	29 kg	56 kg
Working Load Limit	1200 kg	5000 kg	7000 kg
Dimensions	450 mm x 100 mm x 170 mm	475 mm x 245 mm x 140 mm	580 mm x 150 mm x 300 mm
Part #	ACF012ASB	ACF053ASB	ACF070ASB

Crusader Hose Pty Ltd

22 Industry Place, Bayswater VIC 3153 Australia e: sales@crusaderhose.com.au p: +61 3 9720 1100 www.crusaderhose.com.au ^{2412a} Crusader Hose reserves the right to modify any specification as part of ongoing product development and without prior notice.

Contact Crusader Hose to ensure that the current technical data sheets and documentation are used.



